

1. Tandus only
 - A. Provide a certification of compliance with the Carpet and Rug Institute's Green Label Plus Indoor Air Quality program for carpets, cushions, and adhesives
2. Poudre School District approved colors only (**HOPSCOTCH 17201**)
3. INSTALLER - Certified by Tandus and have a minimum of five years experience on installations of similar size and complexity for all projects. Currently Approved Contractors:
Accessories:
 - A. Sub-Floor Filler: 40 pounds Fix-a-Crete plus 5 gallons WFT606 latex and white silica sand, "Webcrete", "LevelCure", or Approved Equal. Use correct product for specific application thickness (to 1/8 inch and 1/8 inch to 1/2 inch).
 - B. Direct Glue Down Adhesive: Recommended by carpet manufacturer.
 - C. Adhesive for Carpet Mounted as Base: discouraged.
 - D. Transition Moldings and Floor Edge Strips: Western Trade Supply (970-226-6933) Part No. CM304 HMF (2 inch width) by Futura. (No substitutions).
 - E. Seam Adhesive: Recommended by carpet manufacturer.
 - F. Contact Adhesive: Compatible with carpet material as recommended by carpet manufacturer releasable type.

- E. Primer:
 1. C-36: New Floors
 2. C-46: Old Concrete

BASE

1. FS SS-W-40 Rubber; top set coved:
 - A. R.C. Musson Rubber Company.
 - B. Roppe Rubber Corporation.
 - C. Burke Industries.
 - D. Johnsonite.
 - E. Approved Equal.
2. Height: 4 inch; 4.5 inch preferred. 6 inch if needed. 18 inch tile not allowed.
3. Thickness: 0.125 thick.
4. Finish: Matte.
5. Length: 4 foot sections.
6. Colors: black is preferred.
7. 1/8 inch thickness x 4 inches high.
8. 6 inch high base required in all toilets. Scribed internal corners.
9. Use topset cove base at all resilient flooring and carpeted locations.
10. Use solid rubber Roppe base. No vinyl base allowed.
11. All floor applications shall include a cove base monolithic with the floor, rubber preferred.
12. Carpet base considered at certain locations.
13. INSTALLATION
 - A. Fit joints tight, straight and vertical. Maintain minimum measurement of 1 foot 6 inches between joints.
 - B. Miter internal corners. External corners shall be job formed - no joints within 2 feet of corner edge.
 - C. Install base on solid backing. Bond tight to wall and floor surfaces.
 - D. Scribe and fit to protruding door frames and other interruptions.

- E. Set cove in sealant to seal joint watertight at linoleum flooring in toilet rooms, and other sanitary conditions.
- F. Adhesive for base shall be a type not affected by heat.

ENTRY MATS – LOCATIONS: Vestibules, exterior entries

- 1. Tandus only
- 2. Color: HOPSCOTCH 17201
- 3. Secure with factory applied adhesive.

ACCESSORIES

- 1. Moisture Barrier: "Top Coat II, 7055" by Installers Best Adhesives, 877-784-2248.
- 2. Provide waterproof primers and adhesives as recommended by the manufacturer of the material being installed o suit material and substrate conditions. Use solvent free type.
- 3. Adhesive to be moisture resistant material suitable for installation over slab on grade.
- 4. Floor Filler: 40 pounds "Fix-a-Crete" plus 5 gallons WFT606 latex and white silica sand, "Webcrete", "Level Cure", or Approved Equal. Use correct product for specific application thickness (to 1/8 inch and 1/8 inch to 1/2 inch).
- 5. Roppe #47 square cove cap at wallcovering sisal edges.
- 6. Fillers for Coved Sheet Goods at Floor/Wall Intersection: plastic.
- 7. Sealant at Cove Base: Single component polysulfide.
- 8. Transition Edging for new tile to new carpet is required.
 - A. (970) 226-6933, Part No. CM304 HMF, 2 inch width by Futura. No Substitutions, a) No rubber or vinyl transitions, use Roppe #159 transition if needed.
- 9. Concrete Slab Primer: Non-staining type as recommended by flooring manufacturer.
- 10. Leveling Compound: Latex type which can be feather edged, as recommended by flooring manufacturer, trowelable consistency for tapering where required.
- 11. Provide sealer over Subfloors

END OF SECTION 09 60 00